

In the specification, at pages 13-14, replace the Brief Description of the Figures with the following:

BRIEF DESCRIPTION OF THE FIGURES

Figure 1 is a perspective view of a preferred embodiment of the instant invention illustrated secured within a vehicle door;

Figure 2 is a partially exploded view of the preferred embodiment illustrated in Figure 1;

Figure 3 is an exploded view of the preferred embodiment of the instant invention;

Figure 4 is section view along lines 1-1 of Figure 1 illustrating the relative motion of the front and back panels with respect to downward motion of the vehicle window;

Figure 5 is a perspective view of an alternative embodiment of the instant invention illustrated secured within a vehicle door;

~~Figure 5A is a perspective view of the embodiment illustrated in Figure 5;~~

~~Figure 5B is a front view of the embodiment illustrated in Figure 5;~~

Figure 5C is a partial front view of the embodiment shown in Figure 5 illustrated with the front panel removed;

Figure 5D is a partial perspective view of the embodiment shown in Figure 5;

~~Figure 5E is a bottom view of the embodiment illustrated in Figure 5;~~

~~Figure 5 is a partial front view of the embodiment shown in Figure 5 illustrating the pivotal movement of the top flap member;~~

Figure 6 is a partially exploded view of the embodiment illustrated in Figure 5;

Figure 7 is section view along lines 2-2 of Figure 5 illustrating the relative motion of the front and back panels with respect to downward motion of the vehicle window;

Figure 8 is a perspective view of an alternative embodiment of the instant invention;

Figure 9 is a perspective view of an alternative embodiment of the instant invention;

Figure 10 is a perspective view of an alternative embodiment of the instant invention;

Figure 11 is a perspective view of an alternative embodiment of the instant invention.